

### GENERAL INFORMATION

Generic Name : Adhesive V-652  
 Technical Name : Adhesive V-652  
 Measurement unit : Kilogram (kg.)  
 Overview : Pressure sensitive Water based adhesive for serigraphy and graphic arts industry, non flammable, environmental friendly

### SPECIFICATIONS

#### Properties

Color: White.  
 Odor: Slight.

Propiedades fisico-químicas	
pH (25°C)	4.0 a 6.0 pH
Viscosity (Brookfield spindle 4, rpm 12, 25°C ± 0.5)	150 – 200 Cps
Density	1.02 g/cm <sup>3</sup>
Total Solids	60% ± 2%
Boiling Point	41°C
Freezing Point	-1°C

### USES AND APPLICATIONS

#### Instructions

**Application Method:** It can be apply by spray or roller (mechanic o manual)

**Surface Treatment:** Clean surfaces from dust, grease, water and oxides.

**Application:** Apply a uniform layer to one or two substrates that will be bond.

**Dry time:** Substrates need to be dried for at least 3 minutes (weather conditions can vary dry time).

**Assembling and Pressure:** Bond surfaces by applying uniform pressure throughout the piece

## **USES**

---

While primarily designed for use with cotton, polyester, non-woven, jeans, textiles, fabrics. Etc.

## **CLEAN UP**

---

In some cases wet adhesive may be removed with water. Dry adhesive cannot be removed from porous substrates such as foam, textiles, and fabrics. It is recommended that users prevent adhesive from getting on surfaces where it's not wanted.

## **OTHER SPECIFICATIONS**

---

### **Available size container**

Adhesive V-652 is available in 11kg, 20kg, 22kg, 200kg and 1,000 kg (5, 50, 250 gallon container size)

## **STORAGE**

---

Close container tightly after use and store in a cool, dry place between 15 and 25° C. Keep out of reach of children and animals. Do not contaminate water or food by storage or disposal.

Adhesive life time is 6 months in an unopened containers.

## **PRECAUTIONARY INFORMATION**

---

Do not ingest. If swallowed, do not induce vomiting. Seek medical attention immediately. Avoid contact with skin and eyes.

## **TRADEMARK**

---

All trademarks in this document are trademarks of WBP COMPANY

## **CERTIFICATION**

---

If you need an special certificate, please contact our technical service department