

GENERAL INFORMATION

Generic Name : Adhesive V-851
 Technical Name : Adhesive V-851
 Measurement unit : Kilogram (kg.)
 Overview : Pressure Sensitive Water based adhesive for label industry, non flammable, environmental friendly

SPECIFICATIONS

Properties

Color: White.
 Odor: Slight.

Propiedades fisico-químicas	
pH (25°C)	4.0 a 6.0 UpH
Viscosity (Brookfield spindle 4, rpm 12, 25°C ± 0.5)	250 – 1000 Cps
Density	1.02 g/cm ³
Total Solids	63% ± 2%
Boiling Point	41°C
Freezing Point	-1°C

USES AND APPLICATIONS

Instructions

Application Method: It can be apply by spray, brush or roller (mechanic o manual)

Surface Treatment: Clean surfaces from dust, grease, water and oxides.

Application: Apply a uniform layer in to the substrate that will be bond.

Dry time: Substrates need to dry for at least 3 to 5 minutes (weather conditions can vary dry time).

Assembling and Pressure: Bond surfaces by applying uniform pressure throughout the piece.

USES

While primarily designed for use with different types of materials like, fabric, polyester fiber, cotton fiber, wood, plastic, glass, steel, cardboard, jute, rubber, leather, vinyl, non-wovens, and other materials.

CLEAN UP

In some cases wet adhesive may be removed with water. Dry adhesive cannot be removed from porous substrates such as foam, textiles, and fabrics. It is recommended that users prevent adhesive from getting on surfaces where it's not wanted.

OTHER SPECIFICATIONS

Available size container

Adhesive V-851 is available in 11 kg, 20 kg, 22 kg, 200 kg and 1,000 kg (5, 50, 250 gallons container size)

STORAGE

Close container tightly after use and store in a cool, dry place between 15 and 25° C. Keep out of reach of children and animals. Do not contaminate water or food by storage or disposal.

Adhesive life time is 6 months in an unopened containers.

PRECAUTIONARY INFORMATION

Do not ingest. If swallowed, do not induce vomiting. Seek medical attention immediately. Avoid contact with skin and eyes.

TRADEMARK

All trademarks in this document are trademarks of WBP COMPANY

CERTIFICATION

If you need an special certificate, please contact our technical service department